




610 S. Maumee St. Tecumseh, MI 49286 | Ph: 517-424-0577

CUSTOM

Universal Tilt/Tele Floor Shift

(Standard measurements are shown)



To customize your column, please download this form & fill in the fields below. Mark the column drawing if necessary, add any additional comments and sign.

Once you are satisfied, save the filled out form and email it to us at sales@ididitinc.com. Directions for submitting can be found here: <http://bit.ly/1c00Ep6>

Alternatively, you can also fax it to us at: 517-424-7293

- Reposition Wire Harness: _____ " From Top of Column
Overall wire harness position is measured from top of adaptor in collapsed position to top of wire harness location. Standard is 14 1/2". Max total is 25", Cruise control max is 20"
- Rotation of Wire Harness: _____ : _____ O'clock (per 1/2 hour)
Rotation starts at 12 o'clock from seating position
- Change Cup Length: _____ " Minimum of 1", Standard is 2 7/8"
Shortened cup lengths may expose internal column wiring
- Tube Diameter (check one): 2" 2 1/4"
- Shaft Length: _____ " Out of tube (Max 8")
- Shaft Type (check one): 1"48 3/4"DD 1"DD 3/4"36
Columns under 22" can only be built using a 3/4" DD output shaft
- Overall Length (from top of adaptor to bottom of shaft in collapsed position): _____ "
- Ignition: YES NO (Ignition not available on aluminum columns)
- What type of Adaptor 5-Bolt 6-Bolt 9-Bolt
Please specify brand in comments section 3-Bolt not available with Tilt/Tele
- Column Finish (check one): Paintable Steel Chrome Black
 Brushed Aluminum Polished Aluminum

Vehicle: _____ Year: _____

Additional Comments: _____

Name: _____

Phone: _____ Email: _____

By typing my name below, I agree to recognize this as my legal signature for this document. The information I have supplied is correct and I assume responsibility for the requests that have been made on this form.

Signature: _____

Date: ____/____/____

Sales Order #: _____